



INTRA KA VAADA



 Loading area (2 690 mm x 1 620 mm (8.8 ft. x 5.3 ft.)



 52 kW (70 hp) power & best-in-class gradeability



Leaf spring suspension (5 leaves in the front & 8 in the rear)



 Electronic power-assisted steering (EPAS)



• Best-in-class fuel efficiency (Gear shift advisor + Eco switch)



• Rated payload of 1300 kg











SPECIFICATIONS	INTRA V30 BSVI
Engine	
Engine	4 Cylinders, 1497 cc DI Engine
Max Engine Output	52 kW @ 4 000 r/min (70 hp)
Max Torque	160 Nm @ 1750-2750 r/min
Weights	
Max GVW	2 565 kg
Payload	1300 kg
Dimensions	
Overall Length	4 460 mm
Wheelbase	2 450 mm
Ground Clearance	170 mm
Cargo Box Dimensions (lxb)	2 690 mm x 1 620 mm (8.8 ft. x 5.3 ft.)
Min TCR	5 250 mm
Steering	
Туре	Electronic power assisted steering
Suspension	
Suspension Front	Semi-elliptical leaf springs - 5 leaves
Suspension Rear	Semi-elliptical leaf springs - 8 leaves
Brakes	
Front	Hydraulic disc brake
Rear	Drum 254 mm dia Rear with LCRV
Tank Capacity	
Diesel Tank	35 L
Tyres	
Tyresize	185 R14 8PR Size
Warranty	
Warranty	2 years / 72 000 km

TO KNOW MORE

TOLL-FREE NUMBER | 1800 209 7979

SMS# <INTRA> to 5616161 #SMS charges as per service provider VISIT OUR WEBSITE www.intra.tatamotors.com

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.



