







 Loading area (2 960 mm x 1620 mm = 9.8 ft x 5.3 ft)



• 59 kW (79 hp) power & best-in-class gradeability



 Leaf spring suspension (2 leaves in the front and 10 in the rear)



• Hydraulic power assisted steering

BADI BACHAT

• Best-in-class fuel efficiency (Gear shift advisor + Eco switch)



Rated payload of 1500 kg

INTRA V50











SPECIFICATIONS	INTRA V50 BSVI
ENGINE	
Engine Capacity	4-cylinder, 1496 cm³ DI Engine
Max. Engine Output	59 kW @ 4 000 r/min (79 hp)
Max. Torque	220 Nm @ 1750-2 500 r/min
WEIGHT	
Gross Vehicle Weight	2 960 kg
Payload	1500 kg
DIMENSIONS	
Wheel Base	2 600 mm
Overall Length	4 734 mm
Load Body (lenght x width)	2 960 mm x 1 620 mm (9.8 feet x 5.3 feet)
Min. Turning Circle Radius	6.0 m
STEERING	
Туре	Hydraulic power assisted steering
SUSPENSION	
Front	Parabolic leaf spring – 2 leaves
Rear	Multileaf Semi-elliptical two stage leaf spring – 10 leaves
PERFORMANCE	
Max. Gradeability	35%
TYRES	
Tyre Size/Type	215/75 R15 8PR (with tube)
AIR CONDITIONED	Optional

TO KNOW MORE

TOLL-FREE NUMBER | 1800 209 7979

SMS# <INTRA> to **5616161**#SMS charges as per service provider

VISIT OUR WEBSITE www.intra.tatamotors.com

The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.

